



LEADER TECNOLOGICO IN SPETTROSCOPIA DAL 1952
...LE SUE ANALISI MERITANO LE NOSTRE "PERFORMANCE"

FINALMENTE, UNO SPETTROFOTOMETRO A INFRA-ROSSO AFFIDABILE, PRECISO E ROBUSTO, GARANTITO SENZA INTERFEROMETRO!

Lo spettrofotometro SAFAS IR600 è uno spettrofotometro a infra-rosso di tipo dispersivo, senza interferometro, quindi robusto, poco sensibile alle vibrazioni, l'umidità e la polvere, e non necessita nessuna manutenzione particolare: ne vuoto da mantenere, ne anti-umidità da rimpiazzare, ecc...

Siamo spiacenti, questa pagina non è ancora disponibile in Italiano...

A RUGGED, RELIABLE AND ACCURATE IR SPECTROPHOTOMETER



Fitted with a grating monochromator, the SAFAS IR600 virtually doesn't require any precaution of use or specific maintenance: no vacuum, no problems for surrounding vibrations or dust, no window or expensive separator to replace, etc... The SAFAS IR600 is the best solution for those who wish to achieve quality analysis in the Infra-Red range without undergoing expensive ownership costs and having to take a lot precautions.

Thanks to its grating monochromator, it doesn't require to calculate a Fourier Transform: you have a direct reading, and the instrument can even achieve fast continuous measurements at a fixed wavelength, which is impossible for a FTIR.

A POWERFUL SOFTWARE

SAFAS IR600 spectrophotometer is driven by a software 100% developed by SAFAS, as easy to use as powerful. An optional version of that software has been developed for those who need to conform to FDA CFR21 part 11.

MANY ACCESSORIES ARE AVAILABLE

SAFAS IR600 is fitted with a standard accessories slider, compatible with most of the accessories on the market. A ZnSe prism enables to quickly measure series of samples (liquids, greases, emulsions, powders...) with minimum preparation. Deposit your sample, start measurements... then clean up: you are ready for the next sample!

AN EXCELLENT PRICE EFFECTIVENESS

SAFAS IR600 is offered at a very interesting price, and will provide a very low ownership cost to your lab'. Feel free to contact us!

Main features of SAFAS IR600

Spectral Range	4000 to 600 cm ⁻¹
Typical resolution	better than 2cm ⁻¹ at 2000cm
Monochromator	grating, CZERNY TURNER mount, guaranteed without interferometer, and no windows to replace !
Sample holder	standard, compatible with most of accessories on the market
Software	for PC external computer, powerful and easy to use (several languages available)

SAFAS - FABBRICANTE DI SPETTROFOTOMETRI (UV, VISIBILE, INFRA-ROSSO, ASSORBIMENTO ATOMICO), SPETTROFLUORIMETRI,
LUMINOMETRI, LETTORI DI MICROPIASTRE, ANALIZZATORI

SAFAS Monaco - Société Anonyme de Fabrication d'Appareillages Scientifiques

Sede e Amministrazione : 10, quai Antoine 1er - MC 98000 Monaco

Depositi : 9, avenue de la Quarantaine - MC 98000 Monaco

Telefono : **+377 99 99 52 52** - Fax : **+377 99 99 52 50**

Servizio assistenza clienti : **+377 99 99 52 52** | eMail: safas@safas.com

© 2007-2015 SAFAS - Tutti i diritti riservati